DXSTOCK 945









DXSTOCK 945

Innovative and reliable Multifunctional Vending Machine, compliant with the concept of industry 4.0.



ADVANTAGES

- 24/7 access.
- ▶ Drop in the consumption of products by **up to 50**%.
- Large capacity, up to 945 compartments in the machine.
- 4 options for loading products into the machine.
- ▶ 21" touch screen with modern and intuitive interface.
- ▶ 9 configurations for height and width of compartments.
- ▶ Built-in RFID reader, barcode and **QR code scanner**.
- Monitoring of current status via the IRSystem web application.
- Modularity allows to combine devices into sets.

DXSYSTEM APPLICATION


We offer proprietary DXSYSTEM software tailored to the individual needs of the customer for each vending machine, which opens up unlimited possibilities for remote process management. DXSYSTEM enables data migration and fast communication between the server and machine.

- possibility of **integration** with systems such as ERP, GERP, SAP, etc.
- generating of automatic reports and orders
- actual preview of the inventories available in the machine
- management of authorisation of employee access to the vending machine



DXSTOCK 945 is a modern and **self-service vending machine** used for product distribution. The rotating, sturdy drum gives you the ability to storage **up to 945 unique items.** Ease of operation is provided by **21**" **touch screen** with modern and intuitive interface. **Four product loading options** enable even faster and simpler filling the machine. The **DXSTOCK 945** has a built-in **RFID reader**, barcode and **QR code scanner**.

TECHNICAL SPECIFICATIONS				
Height [mm]	2 000			
Width [mm]	1 100			
Depth [mm]	840			
Voltage [V]	230 VAC - 50 Hz			
Power usage [W]	5/80			
Max. drum load [kg]	350			
Weight [kg]	530			
Temp. [°C]	from 5 to 70			
DRUM CONFIGURATIONS				



COMPARTMENS CONFIGURATIONS AND DIMENSIONS				
NUMBER OF COMPARTMENTS	A HEIGHT [MM]	B WIDTH [MM]	C DEPTH [MM]	D WIDTH [MM]
945	80	50	295	12
630	80	80	295	18
315	80	160	295	35
495	160	50	295	12
330	160	80	295	18
165	160	160	295	35
315	245	50	295	12
210	245	80	295	18
105	245	160	295	35