



LEDATEL

Solutions for rail and military

Vending machines

Modern vending machines
for **snacks, cold drinks**
and **hot drinks**
with approval for railways



Snack and cold drink vending machine
Hot drink vending machine

ST6 | HS7

Key Features:

- **NAYAX contactless payment** system
- **42 types of snacks** and cold drinks
- **2 coffee bean grinders** allowing the use of two different types or blends of coffee
- **6 containers** for sugar and **instant drinks**
- Internal **fire extinguishing system**
- Large color displays with **touch user interface**



Manufactured
in EU



SPECIFICATION



COFFEE AND HOT DRINKS VENDING MACHINE HS7

Functional parameters:

- Number of coffee grinders | 2
- Number of coffee bean containers | 2
- Number of sugar and instant product containers | 6
- Ingredient container capacity | 4.4 l
- Cup type | Ø 70÷73 mm | Ø 80 mm
- Number of cups | 750 | 550
- Water container capacity | 25 l
- Number of products that can be prepared | 22

User interface:

- Touch screen | 18.5"
- Payment system | NAYAX
- Interface language | Polish | English | German
- Wheelchair compatible | YES

Fire safety:

- Internal fire extinguishing system (Railway devices)

Power supply:

- Power supply range | 220÷240 V AC / 50÷60 Hz / 13.6 A
- Power consumption during operation | 134 Wh (per liter of drink) | 694 Wh (per day in idle mode)

Physical parameters:

- Dimensions | 1805 mm x 655 mm x 770 mm (± 5 mm)
- Weight | 180 kg ± 5%
- Mounting interface | rails (optionally other)
- Operating temperature | 10÷32°C
- Storage temperature | -45÷50°C
- Storage humidity | max. 85%

Both machines meet the requirements of the standards:

- EN 50155:2021, EN 45545-2:2020, EN 61373:2010/AC:2017 and EN 50121-3-2:2016/A1:2019



SNACK AND COLD DRINKS VENDING MACHINE ST6

Functional parameters:

- Number of product compartments | 3÷6
- Number of product shelves | 6 (optionally 7)
- Number of products | max. 42
- Internal temperature range | 2÷18°C

User interface:

- Touch screen | 7"
- Payment system | NAYAX
- Interface language | Polish | English | German

Fire safety:

- Internal fire extinguishing system (Railway devices)

Power supply:

- Power supply range | 220÷240 V AC / 50 Hz / 3.4 A

Physical parameters:

- Dimensions | 1830 mm x 830 mm x 845 mm (± 5 mm)
- Weight | 275 kg ± 5%
- Mounting interface | rails (optionally other)
- Operating temperature | 18÷32°C
- Storage temperature | -45÷50°C
- Storage humidity | max. 65%

